

FS24 (ex 3466)


Sounder with beacon


- Dual-tone sounder with beacon
- High sound power
- LED beacon
- Indoor use
- 24 V power supply
- High quality/price ratio
- EN 54-3 approved

Dual-tone piezoelectric sounder with high acoustic power and LED flashlight. Thanks to its particularly sophisticated aesthetics and compact size, this sounder is suitable for both residential and commercial environments. Current consumption very low. Terminals are split for connection shunting. Suitable both for 12V and 24V systems. It is provided with adhesive writings to be applied on the flashlight reflector. Excellent quality/price ratio.

GENERAL SPECIFICATIONS

| Housing material | Thermoplastic, red color | | | | |
|-----------------------|----------------------------|--|--|--|--|
| Cover material | Thermoplastic, red color | | | | |
| Connection type | (4) terminals for shunting | | | | |
| Dual tone frequency | 450Hz-550Hz ± 10% | | | | |
| | | | | | |
| Operating temperature | -5°C to +50°C | | | | |
| Protection degree | IP 30 | | | | |
| Approval | EN 54-3 | | | | |
| Standard equipment | Adhesive writings | | | | |
| Packaging | 1 pcs./package | | | | |
| · | | | | | |





ORDER CODES

| Code | Rated voltage | Rated current | Acoustic output @ 1 m | Lamp | Flashlight frequency | Color | Package weight | Notes |
|------|------------------|---------------|--------------------------|------------------------|----------------------|-------|-------------------|-------------------------|
| 3466 | 24V DC | 60 mA | 98 dB | High Iuminosity LED | 110 / min | Red | 0,46 kg | With adhesive writings* |

^{*} Provided writings: INCENDIO, FIRE, FUEGO, FOGO





