

ENVIROALERT®



EA-WMFS
Shown with
TEMP-H-S sensor
(sensor sold separately)

Wireless Multi-Function Accessory for EnviroAlert EA800-ip

- Transmission distance of 1,000' (305 m) line-of-sight.
- Set temperature high/low set points on EnviroAlert console.
- Do not put EA-WMFS in freezer/cooler. Use wired sensor.
- Max probe cable run: 1,000' (305 m) [22 AWG twisted pair]

Accessory for EnviroAlert EA800-ip

Specifications

Sensing Range	Remote sensor dependent - requires remote sensor for operation.
Power Requirements	2 - AA Alkaline Batteries or 12 VDC @ <=100mA
Battery Life	Alkaline up to 1 year (not included)
Unit Operating Range	32° to 122° F (0° to 50° C) Non-condensing environment.
Frequency	2.405 GHz - 2.480 GHz, 16 channels. See owner's manual for more information.
Transmission Distance	1,000' (305m) line-of-sight
Weight	0.25 lb (0.11 kg)
Dimensions	3.67 x 2.65 x 1.17" (9.3 x 6.7 x 2.9 cm)
Mounting	Surface Mount

Requires sensor for operation

Accessory sensors:

Detection	Model	Number Range
Temp Ultra Low (White) Stainless Steel	TEMP-UL-S	-112° to 32° F (-80 to 0° C)
Temp Low (Blue) Stainless Steel	TEMP-L-S	-58° to 158° F (-50 to 70° C)
Temp Low (Blue) Waterproof	TEMP-L-W	-58° to 158° F (-50 to 70° C)
Temp High (Red) Stainless Steel	TEMP-H-S	32° to 299° F (0 to 150° C)
Temp High (Red) Waterproof	TEMP-H-W	32° to 221° F (0 to 105° C)
Water Surface Sensor (supervised)	W-S-S	
Water under Carpet (supervised)	W-UC-S	
PS-110 Power Out Alert	PS-110	

N.O./N.C. devices



Visit www.winland.com, call 800.635.4269 or email techsupport@winland.com to learn more.

